



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**05.09.2001 Bulletin 2001/36**

(51) Int Cl.7: **B62M 23/02**

(21) Application number: **01103471.7**

(22) Date of filing: **14.02.2001**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
 MC NL PT SE TR**  
 Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Sakagami, Koji, c/o K.K. Honda Gijutsu  
 Kenkyusho  
 Wako-shi, Saitama (JP)**

(30) Priority: **01.03.2000 JP 2000055085**

(74) Representative: **Liska, Horst, Dr.-Ing. et al  
 Weickmann & Weickmann  
 Patentanwälte  
 Postfach 86 08 20  
 81635 München (DE)**

(71) Applicant: **HONDA GIKEN KOGYO KABUSHIKI  
 KAISHA  
 Minato-ku Tokyo (JP)**

(54) **Motor-driven bicycle**

(57) The invention provides a motor-driven bicycle including an automatic gear shifter, which is capable of improving a shift feeling upon gear-shift and controlling a self-running power of a drive motor determined on the basis of an amount of a self-running operation by a driver as a function of a braking state and a vehicle speed. To achieve this, a motor-driven bicycle includes a drive motor M for generating a self-running power in response to a self-running operation by a driver, a gear shifter connected between the drive motor M and a drive wheel, and means for detecting a vehicle speed. This motor-

driven bicycle further includes a self-running reference duty ratio map 201 for determining a self-running power to be generated by the drive motor M, that is, a duty ratio of an AC exciting current to be supplied to the drive motor M on the basis of an operated amount of a self-running operation by a driver, a gear step of the gear shifter, and a vehicle speed. In the self-running reference duty ratio map 201, a reference duty ratio Dref1 of a drive current to be supplied to the drive motor M at the time of self-running is previously registered as a function of a throttle angle  $\theta$  th detected by a throttle opening sensor 15.




FIG. 2

## Description

**[0001]** The present invention relates to a motor-driven bicycle including a drive motor for generating a self-running power in response to an operated amount of a self-running operation by a driver and an automatic gear shifter, and particularly to the motor-driven bicycle capable of obtaining a desirable gear-shift feeling upon automatic gear-shift.

**[0002]** Unlike a motor-assisted bicycle, called an assist bicycle, including an electric motor for generating an assisting power in response to a leg-power inputted to a crank shaft, wherein a synthetic power of the leg-power and assisting power is transmitted to a drive wheel, a motor-driven bicycle including a drive motor for generating a self-running power in response to, typically, an opening degree of a throttle lever has been proposed, for example, in Japanese Patent Laid-open No. Hei 9-263289.

**[0003]** A motor-driven bicycle, including a stepping gear shifter different from a continuous variable transmission mounted on a conventional motor-driven scooter or the like and an actuator of the stepping gear shifter, has a technical problem that if a difference occurs between output torques at adjacent two of gear steps before and after gear-shift, a desirable gear-shift feeling cannot be obtained.

**[0004]** A first object of the present invention is to solve the above-described problem of the prior art motor-driven bicycle, and to provide a motor-driven bicycle capable of obtaining a desirable gear-shift feeling upon automatic gear-shift.

**[0005]** In the above prior art motor-driven bicycle, since it is not required to generate a self-running power in a state in which a brake lever is being operated during running of the vehicle, the self-running power is limited during operation of the brake lever for keeping the stored energy; however, since the motor-driven bicycle is heavier than a conventional bicycle, at the time of start-up of the vehicle on a slope for example, a self-running power is generated by operating a throttle lever from the state in which the brake lever is being operated for smoothening the start-up of the vehicle.

**[0006]** In the prior art motor-driven bicycle, however, since the drive motor is not controlled on the basis of a braking operation and a vehicle speed, there may occur inconvenience that the drive motor may generate a self-running power although brake operation is being performed during running of the vehicle or the drive motor may be difficult to generate, at the time of start-up of the vehicle, a self-running power from the braking state so as to smoothen the start-up of the vehicle.

**[0007]** A second object of the present invention is to solve the above-described prior art problems, and to provide a motor-driven bicycle capable of controlling a self-running power of a drive motor determined on the basis of an amount of a self-running operation by a driver as a function of a braking state and a vehicle speed.

**[0008]** To achieve the above object, according to the present invention, there is provided a motor-driven bicycle including a drive motor for generating a self-running power in response to a self-running operation by a driver, a gear shifter connected between the drive motor and a drive wheel, and means for detecting a vehicle speed, characterized in that the motor-driven bicycle further includes self-running power determining means for determining a self-running power to be generated by the drive motor on the basis of an operated amount of the self-running operation, a gear step of the gear-shifter, and a vehicle speed.

**[0009]** With the above-described feature, since a self-running power to be generated by the drive motor can be finely set to an optimum value on the basis of the operated amount of a self-running operation, a gear-step of the gear shifter, and a vehicle speed, it is possible to make output torques at adjacent two of gear steps before and after gear-shift correspond to each other upon gear-shift, and hence to obtain a desirable shift feeling.

**[0010]** To achieve the second object, according to the present invention, there is provided a motor-driven bicycle including a drive motor for generating a self-running power in response to an amount of a self-running operation by a driver, characterized in that the bicycle includes during-braking control means for controlling the self-running power on the basis of a braking operation and a vehicle speed.

**[0011]** With the above-described feature, since a self-running power determined on the basis of an amount of a self-running operation by a driver can be controlled by a braking operation and a vehicle speed, the self-running power at the time of braking operation can be optimized.

**[0012]** The present invention exhibits the following effects:

(1) Since a self-running power to be generated by the drive motor can be set to an optimum value with the operated amount of a self-running operation, a gear step of the gear shifter, and a vehicle speed taken as parameters, it is possible to make output torques at adjacent two of gear steps before and after gear-shift correspond to each other upon gear-shift, and hence to obtain a desirable shift feeling.

(2) Since a vehicle speed is detected on the basis of a detection signal of the sensor provided for detecting a rotational speed of the crank pedals, it is possible to eliminate the need of provision of a vehicle speed sensor.

(3) Since a vehicle speed is detected on the basis of a rotational speed of the drive motor and a gear step of the gear shifter, it is possible to eliminate the need of provision of a vehicle speed sensor.

(4) Since a gear step of the gear shifter is detected on the basis of a rotational speed of the drive motor and a vehicle speed, it is possible to eliminate the need of provision of a vehicle speed sensor.

(5) Since a target value of self-running output of the drive motor determined in response to the operated amount of a self-running operation is obtained from the mapping table, it is possible to easily perform the setting of the target value, the change thereof, and the like.

(6) Since a self-running power determined on the basis of an amount of a self-running operation by a driver can be controlled on the basis of the presence or absence of braking operation and a vehicle speed, the self-running power at the time of braking operation can be optimized.

(7) Since the drive motor is allowed to generate, when a braking operation is detected during running of the vehicle, a drive force being small enough to bring about a state in which no load is apparently applied to the drive motor, it is possible to prevent useless power consumption due to operation of the drive motor during braking operation. Further, since the drive motor does not cause any rotational load even during braking operation, it is possible to obtain a natural brake feeling corresponding to an operated amount of the brake.

(8) Since the drive motor is allowed to generate, when a self-running operation is performed in a vehicle stoppage state in which braking operation is being performed, a drive force corresponding to an amount of the self-running operation, it is possible to prevent "slip-down" of the vehicle upon start-up of the vehicle on a slope.

(9) Since a self-running power generated by the drive motor is, when a self-running operation is performed in a vehicle stoppage state in which braking operation is being performed, gradually increased up to a value corresponding to an amount of the self-running operation, it is possible to obtain smooth acceleration feeling.

**[0013]** Hereinafter, the present invention will be described in detail with reference to the accompanying drawings.

**[0014]** Fig. 1 is a view showing a configuration of a motor-driven bicycle to which the present invention is applied.

**[0015]** Fig. 2 is a block diagram of a controller shown in FIG. 1.

**[0016]** Fig. 3 is a flow chart showing an operation of the controller.

**[0017]** Fig. 4 is a flow chart showing a rapid acceleration suppressing control.

ation suppressing control.

**[0018]** Fig. 5 is a flow chart showing a gear-shift control.

**[0019]** Fig. 6 is a flow chart showing a motor output limiting control.

**[0020]** Fig. 7 is a view showing a gear-shift control method upon shift-up from the "second speed" to the "third speed".

**[0021]** Fig. 8 is a view showing a gear-shift control method upon shift-down from the "second speed" to the "first speed".

**[0022]** Fig. 9 is a view showing a gear-shift control method upon shift-up from the "first speed" to the "second speed".

**[0023]** Fig. 10 is a view showing a method of setting a gear-shift vehicle speed Vch23 between the "second speed" and the "third speed".

**[0024]** Fig. 11 is a view showing a method of setting a gear-shift vehicle speed Vchl2 between the "first speed" and the "second speed".

**[0025]** Fig. 12 is a block diagram of another embodiment of the controller shown in FIG. 1.

**[0026]** FIG. 1 is a view showing a configuration of a motor-driven bicycle to which the present invention is applied. In this figure, parts not necessary for description of the present invention are omitted.

**[0027]** Like a conventional bicycle, a handlebar 10 includes at its left end portion a brake lever 11 for a rear wheel and at its right end portion a brake lever 13 for a front wheel. The handlebar 10 also includes in the vicinity of fulcrums of the brake levers 11 and 13 brake switches 12 and 14 for detecting operational states of the brake levers 11 and 13 and outputting during-braking signals SB. The handlebar 10 further includes at its right end portion a throttle lever 16 as self-running input means for indicating generation of a self-running power to a drive motor M (which will be described later), and a throttle opening sensor 15 for detecting an operated angle  $\theta$ th as an operated amount.

**[0028]** A body frame has at its central portion a power unit 2 for selectively carrying out "self-running" by the drive motor M and "assist-running" for assisting a leg power by a drive force of the drive motor M. A leg-power inputted to a crank shaft 30 from left and right crank pedals 38L and 38R is transmitted via a one-way clutch 26 to a large-diameter gear 36 coaxially connected to the crank shaft 30, and is further transmitted via a first idle shaft 35 to an output shaft 34. The one-way clutch 26 allows transmission of a rotational force from the crank shaft 30 to the large-diameter gear 36, and prohibits transmission of a rotational force from the large-diameter gear 36 to the crank shaft 30.

**[0029]** A drive force generated by the drive motor M is transmitted via a second idle shaft 36 to an idle gear 37. The idle gear 37 is connected via a one-way clutch 29 to the first idle shaft 35. The drive force having been transmitted to the idle gear 37 is transmitted via the first idle shaft 35 to the output shaft 34. One end of the output

shaft 34 is exposed to the outside of the power unit 2, and a drive sprocket 32 is connected to the exposed end of the output shaft 34.

**[0030]** A motor rotation sensor 25 detects a rotational speed NM of the drive motor M. A temperature sensor 24 detects a temperature TM of the drive motor M. A leg-power sensor 23 detects a leg-power inputted to the crank shaft 30. A crank pedal rotation sensor 22 detects a rotational speed of the crank pedals 38 (38L, 38R) on the basis of the rotational speed of the large-diameter gear 36. A current sensor 27 detects a drive current IM of the drive motor M. Output signals of the above-described sensors are inputted to a controller 20.

**[0031]** A driven sprocket 33 and a four-step gear shifter 19 are provided on an axle of a rear wheel 31 as a drive wheel. The drive sprocket 32 of the output shaft 34 is connected to the driven sprocket 33 via a chain 39. An automatic gear-shift actuator 17 outputs a gear-shift step signal DG representative of a gear-shift step in response to a gear-shift command SG outputted from the controller 20. The gear shifter 19 is driven on the basis of the gear-shift step signal DG. A rotational speed V of the rear wheel 31 is detected by a vehicle speed sensor 18, and a signal of the vehicle speed sensor 18 is inputted to the controller 20.

**[0032]** FIG. 2 is a block diagram showing a configuration of a main portion of the controller 20. In this figure, the same characters as those shown in FIG. 1 designate the same or similar parts.

**[0033]** In a self-running reference duty ratio map 201, a reference duty ratio Dref1 of a drive current IM to be supplied to the drive motor M upon self-running is previously registered in the form of a mapping table with the throttle opening angle  $\theta_{th}$  detected by the throttle opening sensor 15, the vehicle speed V, and a gear step G taken as parameters.

**[0034]** In an assist-running reference duty ratio map 202, a reference duty ratio Dref2 of the drive current IM to be supplied to the drive motor M upon assist-running is previously registered in the form of a mapping table with the leg-power F detected by the leg-power sensor 23 and the vehicle speed V detected by the vehicle speed sensor 18 taken as parameters.

**[0035]** It should be noted that in place of detection of the vehicle speed V by the vehicle speed sensor 18, the vehicle speed V may be detected, by a vehicle speed detecting portion 213 additionally provided, on the basis of the gear-shift step signal DG, which is representative of the gear-shift step G and which is outputted from the automatic gear-shift actuator 17, and the motor rotational speed.

**[0036]** An acceleration detecting portion 203 detects an acceleration  $\Delta V$  on the basis of a rate of change in vehicle speed V with elapsed time. A gear step deciding portion 204 decides the present gear step G on the basis of the detected vehicle speed V and motor rotational speed NM. A rapid acceleration suppressing control portion 205 compares the detected acceleration  $\Delta V$  with

a reference acceleration  $\Delta V_{ref}$ , and instructs, if the detected acceleration  $\Delta V$  is more than the reference acceleration  $\Delta V_{ref}$ , a duty ratio correcting portion 208 (which will be described later) to correct a duty ratio so as to suppress rapid acceleration.

**[0037]** Referring to a gear shifting vehicle speed ( $V_{ch}$ ) data table 206a, a gear-shift control portion 206 decides, on the basis of the detected acceleration  $\Delta V$  and vehicle speed V and the present gear step G decided by the gear step deciding portion 204, whether or not the present running state is a gear-shift timing state. The decided result is supplied to the duty ratio correcting portion 208 and is also outputted to the gear-shift actuator 17.

**[0038]** A non-riding self-running deciding portion 207 decides, on the basis of the present gear step G and motor rotational speed NM, whether or not the present self-running operation is performed in the driver's non-riding state. If it is decided that the self-running operation is performed in the driver's non-riding state, a hand-pushing drive control portion 211 instructs the duty ratio correcting portion 208 to correct a duty ratio so as to generate a self-running power corresponding to a walking speed.

**[0039]** A during-braking control portion 210 instructs the duty ratio correcting portion 208 to correct a duty ratio so as to control a self-running power on the basis of the presence or absence of a braking operation and the vehicle speed V. To be more specific, if the on-states of the brake switches 12 and 14 are detected during running of the vehicle, the during-braking control portion 210 instructs the duty ratio correcting portion 208 to correct a duty ratio so as to allow the drive motor M to generate a drive force being small enough to bring about a state in which no load is apparently applied to the drive motor M. Meanwhile, if a self-running operation is performed in a vehicle stoppage state in which the brake switches 12 and 14 are in the on-states, the during-braking control portion 210 instructs the duty ratio correcting portion 208 to correct a duty ratio so as to allow the drive motor M to generate a drive force corresponding to an operated amount of the self-running operation.

**[0040]** A motor output limiting portion 209 monitors an operational state of the drive motor M on the basis of the drive current IM of the drive motor M detected by the current sensor 27 and the temperature TM of the drive motor M detected by the temperature sensor 24, and instructs, if the drive motor M is in a severe operational state, the duty ratio correcting portion 208 to correct a duty ratio so as to limit the self-running power.

**[0041]** The duty ratio correcting portion 208 corrects, as will be described in detail later, the reference duty ratio Dref1 or Dref2 obtained from the duty ratio map 201 or 202 on the basis of the instructions supplied from the rapid acceleration suppressing control portion 205, the gear-shift control portion 206, the hand-pushing control portion 211, the during-braking control portion 210, and the motor output limiting portion 209, and outputs

the corrected result as a target duty ratio DM.

[0042] A method of controlling the drive motor M upon self-running by the controller 20 will be described with reference to a flow chart shown in FIG. 3.

[0043] In step S11, an opening angle  $\theta$ th of the throttle lever 16 is detected as an operated amount of the self-running operation by the throttle opening sensor 15; a vehicle speed V is detected by a vehicle speed sensor 18; and a rotational speed NM of the drive motor M is detected by the motor rotation sensor 25. In step S12, an acceleration  $\Delta V$  is calculated on the basis of the vehicle speed V detected in step S11 by the acceleration detecting portion 203. In step S13, the present gear step G is decided on the basis of a correlation between the vehicle speed V and the motor rotational speed NM by the gear step deciding portion 204. It should be noted that the present gear step G may be decided on the basis of the gear-shift step signal DG outputted from the automatic gear-shift actuator 17.

[0044] In step S14, a drive current IM of the drive motor M is detected by the current sensor 27, and a temperature TM of the drive motor M is detected by the temperature sensor 24. In step S15, a reference duty ratio Dref1 upon self-running is retrieved from the duty ratio map 201 for self-running on the basis of the throttle opening angle  $\theta$ th and vehicle speed V detected in step S11 and the present gear step G decided in step S13.

[0045] In step S16, on the basis of the states of the brake switches 12 and 14, it is decided by the during-braking control portion 210 whether or not a braking operation has been performed. If it is decided that the braking operation has not been performed, the process goes on to step S17. In step S17, on the basis of an increase ratio  $\Delta NM$  of the motor rotational speed NM, it is decided by the non-riding self-running deciding portion 207 whether or not the driver has operated the throttle lever 16 in the driver's non-riding state. If the increase ratio  $\Delta NM$  of the motor rotational speed NM is a reference increase ratio  $\Delta Nref$  or more, it is decided that the driver has operated the throttle lever 16 in the driver's non-riding state, and the process goes on to step S24. If the increase ratio  $\Delta NM$  is less than the reference increase ratio  $\Delta Nref$ , it is decided that the driver has operated the throttle lever 16 in the driver's riding state, and the process goes on to step S18.

[0046] The parameter for deciding whether or not the driver has operated the throttle lever 16 in the driver's non-riding state is not limited to the above-described increase ratio  $\Delta NM$  of the motor rotational speed NM. For example, the acceleration  $\Delta V$  may be used as the decision parameter. In this case, if the acceleration  $\Delta V$  is larger than a reference acceleration, it may be decided that the driver has operated the throttle lever 16 in the driver's non-riding state. Alternatively, a change ratio of the drive current of the drive motor M may be used as the decision parameter. In this case, if the change ratio of current is larger than a reference change ratio of current, it may be decided that the driver has operated the

throttle lever 16 in the driver's non-riding state.

[0047] In this way, according to this embodiment, it is decided, on the basis of the increase ratio of the motor rotational speed, acceleration of the vehicle, or the change ratio of a drive current of the drive motor, whether or not the self-running operation is performed in the driver's non-riding state, and accordingly, it is possible to eliminate the need of providing a sensor or a switch for detecting the driver's non-riding state.

[0048] In step S18, a routine of "rapid acceleration suppressing control" for ensuring a sufficient acceleration performance while suppressing rapid acceleration is executed.

[0049] FIG. 4 is a flow chart indicating a control content of the "rapid acceleration suppressing control". The control content is determined such that an acceleration corresponding to an operated amount of the throttle lever 16 can be obtained irrespective of a road surface state, a deadweight, and the like by controlling a self-running power of the drive motor M on the basis of a correlation between an operated amount of the throttle lever 16 and an acceleration.

[0050] In step S181, the present acceleration  $\Delta V$  is compared with a reference acceleration  $\Delta Vref$  by the rapid acceleration suppressing control portion 205. If the acceleration  $\Delta V$  is more than the reference acceleration  $\Delta Vref$ , it is decided that the vehicle is in the rapid acceleration state, and the process goes on to step S182. In step S182, the reference duty ratio Dref1 retrieved from the duty ratio map 201 upon self-running is multiplied by a correction coefficient smaller than "1" by the duty ratio correcting portion 208, and the calculated result is taken as a target duty ratio DM.

[0051] In this embodiment, the correction coefficient is defined as " $0.9^{k1}$ ", and the initial value of the exponent k1 is set to "1". Accordingly, in the initial state, a value being 0.9 times the reference duty ratio Dref1 decided by the map 201 is registered as the target duty ratio DM. In step S183, the value of the exponent k1 is incremented by "1". In step S184, a rapid acceleration suppressing flag F1 is set to "1".

[0052] After that, since the above steps are repeated to increase the value of the exponent k1 until it is decided in step S181 that the acceleration  $\Delta V$  is less than the reference acceleration  $\Delta Vref$ , the target duty ratio DM is gradually reduced depending on the value of the exponent k1.

[0053] If it is decided in step S181, as a result of gradually reducing the target duty ratio DM, that the acceleration  $\Delta V$  is less than the reference acceleration  $\Delta Vref$ , the process goes on to step S185 in which it is decided that the rapid acceleration suppressing flag F1 is "1". If it is decided that the flag F1 is set to "1", the process goes on to step S186 in which the duty ratio having been gradually reduced in step S182 is gradually increased.

[0054] In step S186, the present target duty ratio DM is multiplied by a correction coefficient smaller than "1", and the calculated result is taken as a new target duty

ratio DM. In this embodiment, the correction coefficient is defined as a value of  $0.9^{k2}$ , and the initial value of the exponent  $k2$  is set to "5". In the initial state, a value being 0.59 (= 0.95) times the target duty ratio DM is taken as a target duty ratio DM.

**[0055]** In step S187, it is decided whether or not the exponent  $k2$  is reduced to "0". Since the exponent  $k2$  is "5" in the initial state, the process goes on to step S188. In step S188, the value of the exponent  $k2$  is decremented by "1". If it is decided in step S187 that the exponent  $k2$  is "0", the process goes on to step S189 in which the rapid acceleration suppressing flag F1 is reset, thereby ending the routine of "rapid acceleration suppressing control" shown in FIG. 4.

**[0056]** In this way, according to this embodiment, if the acceleration  $\Delta V$  is more than the reference acceleration  $\Delta V_{ref}$ , the correction coefficient is, in step S182, gradually reduced for gradually reducing the target duty ratio DM, and thereafter, if the acceleration  $\Delta V$  is less than the reference acceleration  $\Delta V_{ref}$ , the correction coefficient is, in step S186, gradually increased for gradually increasing the target duty ratio DM, thereby compensating for the above-described gradually reduced amount of the target duty ratio DM. Accordingly, it is possible to obtain a sufficient acceleration performance while suppressing rapid acceleration.

**[0057]** Referring again to FIG. 3, in step S19, it is decided by the gear-shift control portion 206 whether or not automatic gear-shift should be performed. If an absolute value of a difference between the present vehicle speed V and a gear-shift vehicle speed Vch stored in the gear-shift vehicle speed data table 206a for each gear step is less than a reference speed  $V_A$ , the process goes on to step S20 in which a "gear-shift control" is executed for automatic gear-shift. As the gear-shift vehicle speed Vch, a gear-shift vehicle speed Vch12 indicating a gear-shift timing between "first speed"/ "second speed", a gear-shift vehicle speed Vch23 indicating a gear-shift timing between "second speed"/ "third speed", and a gear-shift vehicle speed Vch34 indicating a gear-shift timing between "third speed"/ "fourth speed" are registered. Either of the gear-shift vehicle speeds Vch12, Vch23, and Vch34 is selected on the basis of the present gear step G.

**[0058]** FIG. 5 is a flow chart indicating the routine of the "gear-shift control", which mainly shows the operation of the gear-shift control portion 206.

**[0059]** In step S201, it is decided whether or not a variation in torque caused by gear-shift is increased or decreased. For example, upon shift-up from the "second speed" to the "third speed", as shown in FIG. 7, a torque at the "third speed" is larger than that of the "second speed" at the gear-shift vehicle speed Vch23, and accordingly, it is decided in step S201 that the torque is increased after gear-shift, and the process goes on to step S202. Similarly, upon shift-down from the "second speed" to the "first speed", as shown in FIG. 8, a torque at the "first speed" is larger than that of the "second

speed" at the gear-shift vehicle speed Vch12, and accordingly, it is decided in step S201 that the torque is increased after gear-shift, and the process goes on to step S202.

5 **[0060]** In step S202, referring to the gear-shift vehicle speed data table 206a, the gear-shift control portion 206 decides whether or not the present vehicle speed V reaches a predetermined gear-shift vehicle speed Vch corresponding to the present gear step. Here, if it is decided that, as shown in FIG. 7, the vehicle speed V reaches the gear-shift vehicle speed Vch23 during running at the "second speed" and thereby the timing of shift-up to the "third speed" comes, the process goes on to step S203 in which the gear-shift actuator 17 is driven for gear-shift (shift-up). In step S204, the present target duty ratio DM is multiplied by a correction coefficient smaller than "1", and the calculated result is taken as a new target duty ratio DM.

**[0061]** According to this embodiment, the correction coefficient is defined as  $0.9^{k3}$ , and the initial value of the exponent  $k3$  is set to "5". Accordingly, in the initial state, a value being 0.59 times (= 0.95) the present target duty ratio DM is taken as a target duty ratio DM. As a result, as shown in FIG. 7, a torque immediately after shift-up to the "third speed" is lowered to the same level as that of a torque at the "second speed", with a result that it is possible to obtain a desirable shift feeling.

**[0062]** In step S205, it is decided whether or not the exponent  $k3$  is "0". Since the exponent  $k3$  is "5" in the initial state, the process goes on to step S207 in which the exponent  $k3$  is decremented by "1".

**[0063]** After that, the above-described steps are repeated, to gradually reduce the value of exponent  $k3$ , thereby gradually reducing the target duty ratio DM. Accordingly, as shown in FIG. 7, a self-running power of the drive motor M is rapidly reduced at the gear-shift vehicle speed Vch23, and then gradually increased to be returned to the original target duty ratio DM, thereby obtaining a proper torque corresponding to the gear step.

**[0064]** Similarly, as shown in FIG. 8, even in the case where the vehicle speed V is lowered to the gear-shift vehicle speed Vch12 during running at the "second speed" to be thus shifted down to the "first speed", the target duty ratio DM is reduced such that a torque immediately after shift-down to the "first speed" is reduced to the same level as that of a torque at the "second speed", and then the target duty ratio DM is gradually increased to be returned to the original target duty ratio DM, thereby obtaining a desirable shift feeling.

**[0065]** On the other hand, upon shift-up from the "first speed" to the "second speed", as shown in FIG. 9, since a torque at the "second speed" is smaller than a torque at the "first speed" at the gear-shift vehicle speed Vch12, it is decided in step S201 that the torque is reduced after gear-shift, and the process goes on to step S208 in which it is decided whether or not the present vehicle speed V reaches a predetermined gear-shift vehicle

speed  $V_{ch12}$ . If it is decided that the vehicle speed does not reach the gear-shift vehicle speed  $V_{ch12}$ , the process goes on to step S209 in which the present target duty ratio DM is multiplied by a correction coefficient smaller than "1" and the calculated result is taken as a new target duty ratio DM.

[0066] In this embodiment, the correction coefficient is defined as " $0.9^{k4}$ ", and the initial value of the exponent  $k4$  is set to "1". Accordingly, in the initial state, a value being 0.9 times the present target duty ratio DM is taken as a target duty ratio. In step S210, the exponent  $k4$  is incremented by "1".

[0067] After that, the above-described steps are repeated until it is decided in step S208 that the vehicle speed  $V$  reaches the gear-shift vehicle speed  $V_{ch12}$ , whereby the target duty ratio DM is gradually reduced according to the value of the exponent  $k4$ . Accordingly, as shown in FIG. 9, the torque is gradually reduced.

[0068] If it is decided in step S208 that the vehicle speed  $V$  reaches the gear-shift vehicle speed  $V_{ch12}$ , the process goes on to step S211 in which the gear-shift actuator is driven for gear-shift. At this time, according to this embodiment, since a torque at the "first speed" is reduced to the same level as that of a torque at the "second speed" as shown in FIG. 9, that is, no difference in output torque lies between before and after gear-shift, it is possible to obtain a desirable shift feeling. In step S212, the exponent  $k4$  is set to "1", thereby completing the routine of the "gear-shift control" shown in FIG. 5.

[0069] In the above description, to improve the shift feeling upon gear-shift, the duty ratio of a current supplied to the drive motor M is corrected such that torques of adjacent two of gear steps before and after gear-shift are made to substantially correspond to each other, the present invention is not limited thereto. For example, as shown in FIGS. 10 and 11, the gear-shift vehicle speed  $V_{ch}$ , typically,  $V_{ch12}$  or  $V_{ch23}$  may be set to a speed at which torque curves of adjacent two of gear steps before and after gear-shift intersect each other, or a neighborhood of the speed. With this configuration, it is also possible to improve the shift feeling upon gear-shift.

[0070] Referring again to FIG. 3, in step S23, a routine of "motor output limiting control" for preventing a severe operation of the drive motor is executed. The "motor output limiting control" will be described below with reference to a flow chart shown in FIG. 6.

[0071] In step S231, on the basis of a motor drive current IM detected by the current sensor 27 and the present target duty ratio DM, the present output  $P_{out}$  of the drive motor M is calculated. In step S232, the present output  $P_{out}$  of the drive motor M is compared with a specific maximum output  $P_{max}$ . The maximum output  $P_{max}$  is preferably set to a value being about two times the maximum rating of the drive motor M and is, in this embodiment, set to a value being 1.5 times the maximum rating.

[0072] Here, if it is decided in step S232 that the present output  $P_{out}$  is equal to or more than the maxi-

mum output  $P_{max}$ , the process goes on to step S233 in which the target duty ratio DM is set to a specific maximum value  $D_{max}$ . In step S234, a temperature TM of the drive motor M detected by the temperature sensor 24 is compared with a reference temperature  $T_{ref}$ . In this embodiment, the reference temperature  $T_{ref}$  is set to 90°C.

[0073] Here, if the temperature TM is the reference temperature  $T_{ref}$  or more, the process goes on to step S235 in which the present target duty ratio DM is multiplied by a correction coefficient smaller than "1" and the calculated result is taken as a new target duty ratio DM. In this embodiment, the correction coefficient is defined as " $0.5^{k5}$ ", and the initial value of the exponent  $k5$  is set to "1". Accordingly, a value being 0.5 times the present target duty ratio DM is taken as a target duty ratio DM. In step S236, the exponent  $k5$  is incremented by "1".

[0074] On the other hand, if it is decided in step S234 that the temperature TM is less than the reference temperature  $T_{ref}$ , the process goes on to step S236 in which the exponent  $k5$  is set to the initial value "1".

[0075] In this way, according to this embodiment, since the output of the drive motor M is limited and also if the temperature of the drive motor M is increased, the target duty ratio DM is gradually reduced, it is possible to prevent a severe operation of the drive motor M. Also, since the upper limit of the output of the drive motor M lies within a range being two times the rating of the drive motor M, it is possible to obtain a self-running power from the drive motor M without a severe operation of the drive motor M.

[0076] Referring again to FIG. 3, in step S25, a control of a current of the drive motor M based on the target duty ratio thus determined is executed.

[0077] Additionally, if it is decided in step S16 whether or not either of the brake switches 12 and 14 is in the on-state, that is, the vehicle is on braking, the process goes on to step S21. In step S21, it is decided, on the basis of the vehicle speed  $V$ , whether or not the vehicle is on running.

[0078] Here, if the vehicle speed  $V$  is larger than "0", it is decided in step S21 that the vehicle is on running, and the process goes on to step S22. In step S22, a value being 20% (or which may be 0%) of the present target duty ratio DM, or a value being 20% (or which may be 0%) of the maximum value  $D_{max}$  of the target duty ratio is set as a target duty ratio DM for allowing the drive motor M to generate a drive force being small enough to bring about a state in which no load is apparently applied to the drive motor M.

[0079] If it is decided in step S21 that the vehicle is on stoppage, the process goes on to step S186 of the above-described routine of "rapid acceleration suppressing control" shown in FIG. 4. As a result, the target duty ratio DM is rapidly reduced, and then gradually increased.

[0080] In this way, according to this embodiment, if a self-running operation is performed in a stoppage state

of the vehicle with braking actuated, a self-running power to be generated by the drive motor is gradually increased to a value corresponding to an operated amount of self-running. it is possible to prevent "slip-down" of the vehicle upon start-up of the vehicle on a slope.

**[0081]** It is decided in step S17 that the vehicle is in the driver's non-riding state, the process goes on to step S24. In step S24, to allow the drive motor M to generate a self-running power optimum for hand-pushing drive of the vehicle, a value being 20% of the present target duty ratio DM, or a value being 20% of the maximum value Dmax of the target duty ratio is set as a new target duty ratio DM.

**[0082]** In this way, according to this embodiment, since a self-running power matched to a walking speed can be generated by using the self-running operation input means (throttle lever 16) for generating a usual self-running power, the motor-drive bicycle in this embodiment is allowed to achieve a self-running function matched to a walking speed without provision of a plurality of self-running operation input means.

**[0083]** Further, according to this embodiment, it is decided whether or not a self-running operation is performed in the driver's non-riding state, and a self-running power matched to a walking speed is generated only when it is decided that the self-running operation is performed in the driver's non-riding state, and accordingly, it is possible to eliminate an inconvenience that a self-running power matched to a walking speed is outputted in the driver's riding state.

**[0084]** In the above-described embodiment, the rotational speed of the drive wheel 31 is directly detected by the vehicle speed sensor 18 and the vehicle speed V is detected on the basis of the rotational speed of the drive wheel 31; however, the present invention is not limited thereto. For example, the vehicle speed V may be calculated on the basis of the rotational speed NM of the drive motor M detected by the motor rotation sensor 25 and the gear step G. Alternatively, the vehicle speed V may be calculated on the basis of the rotational speed of the crank pedals 38 detected by the crank pedal rotation sensor 22 and the gear step G.

**[0085]** In the above-described embodiment, the reference duty ratio Drefl of the drive current IM to be supplied to the drive motor M during self-running is registered, in the self-running reference duty ratio map 201, as the function of the throttle opening angle  $\theta_{th}$ , the vehicle speed V, and the gear step G; however, the present invention is not limited thereto. For example, as shown in FIG. 12, only a relationship between the reference duty ratio Drefl and the throttle opening angle  $\theta_{th}$  may be registered, as a map, in the self-running reference duty ratio map 201, and the reference duty ratio Drefl retrieved on the basis of the throttle opening angle  $\theta_{th}$  may be suitably corrected on the basis of the vehicle speed V and the gear step G by the correcting portion 213.

**[0086]** The invention provides a motor-driven bicycle

including an automatic gear shifter, which is capable of improving a shift feeling upon gear-shift and controlling a self-running power of a drive motor determined on the basis of an amount of a self-running operation by a driver as a function of a braking state and a vehicle speed. To achieve this, a motor-driven bicycle includes a drive motor M for generating a self-running power in response to a self-running operation by a driver, a gear shifter connected between the drive motor M and a drive wheel, and means for detecting a vehicle speed. This motor-driven bicycle further includes a self-running reference duty ratio map 201 for determining a self-running power to be generated by the drive motor M, that is, a duty ratio of an AC exciting current to be supplied to the drive motor M on the basis of an operated amount of a self-running operation by a driver, a gear step of the gear shifter, and a vehicle speed. In the self-running reference duty ratio map 201, a reference duty ratio Drefl of a drive current to be supplied to the drive motor M at the time of self-running is previously registered as a function of a throttle angle  $\theta_{th}$  detected by a throttle opening sensor 15. A during-braking control portion 210 decides whether or not braking operation is performed on the basis of the states of brake switches 12 and 14, and receives a vehicle speed V detected by a vehicle speed sensor 18. A duty ratio correcting portion 208 corrects the reference duty ratio Drefl obtained from the duty ratio map 201 on the basis of a control signal from the during-braking control portion 210.

## Claims

1. A motor-driven bicycle including a drive motor (M) for generating a self-running power in response to a self-running operation by a driver, a gear shifter (19) connected between said drive motor (M) and a drive wheel (31), and means for detecting a vehicle speed, **characterized in that**

said motor-driven bicycle further includes self-running power determining means (20) for determining a self-running power to be generated by said drive motor on the basis of an operated amount of the self-running operation, a gear step of said gear-shifter, and a vehicle speed (V).

2. A motor-driven bicycle according to claim 1, further including:


crank pedals (38L,R)

an output shaft (34) to which a drive force generated by said drive motor (M) is transmitted; a rotator (36) connected between said crank pedals and said output shaft, said rotator being allowed to receive a leg-power inputted from said crank pedals and the drive force inputted to said output shaft and to rotate by the leg-power and the drive force and not allowed to



- rotate said crank pedals accompanied by its rotation; and  
a crank sensor (22) for detecting a rotational speed of said rotator;  
wherein the vehicle speed (V) is detected on the basis of the rotational speed of said rotator detected by said crank sensor.
3. A motor-driven bicycle according to claim 1, further including a rotation sensor (25) for detecting a rotational speed of said drive motor (M), wherein the vehicle speed (V) is detected on the basis of the rotational speed of said drive motor and a gear step of said gear shifter (19).
  4. A motor-driven bicycle according to claim 1, further including a rotation sensor (25) for detecting a rotational speed of said drive motor (M), wherein the gear step of said gear shifter (19) is decided on the basis of the rotational speed of said drive motor and the vehicle speed.
  5. A motor-driven bicycle according to claim 1, wherein said self-running determining means (20) has a mapping table (201) for giving a self-running power to be generated by said drive motor (M), which power corresponds to each gear step of said gear shifter, with the operated amount of the self-running operation and the vehicle speed taken as parameters.
  6. A motor-driven bicycle, wherein said self-running power determining means (20) includes:
    - a mapping table (201) for giving a self-running power to be generated by said drive motor (M) with the operated amount of the self-running operation taken as parameters; and
    - correcting means (208) for correcting the self-running power given by said mapping table (201) on the basis of the vehicle speed and a gear step of said gear shifter.
  7. A motor-driven bicycle according to claim 5 or 6, wherein the self-running power generated by said drive motor (M) is controlled by varying a duty ratio (Dref1) of an AC exciting current to be supplied to said drive motor, and a duty ratio (Dref2) of the AC exciting current corresponding to a specific self-running power is registered in said mapping table.
  8. A motor-driven bicycle including a drive motor for generating a self-running power in response to an amount of a self-running operation by a driver, characterized in that
    - said bicycle includes during-braking control means (210) for controlling the self-running power on the basis of a braking operation and a vehicle speed (V).
  9. A motor-driven bicycle according to claim 8, wherein when the braking operation is detected during running of the vehicle, said during-braking control means (210) allows said drive motor (M) to generate a drive force being small enough to bring about a state in which no load is apparently applied to said drive motor.
  10. A motor-driven bicycle according to claim 8 or 9, wherein when the self-running operation is performed in a vehicle stoppage state in which the braking operation is performed, said during-braking control means (210) allows said drive motor to generate a drive force corresponding to an amount of the self-running operation.
  11. A motor-driven bicycle according to claim 9, wherein the drive force being small enough to bring about a state in which no load is apparently applied to said drive motor is a value allowing self-running at a walking speed or "0".
  12. A motor-driven bicycle according to claim 10, wherein when the self-running operation is performed from the vehicle stoppage state in which the braking operation is performed, said during-braking control means (210) gradually increases the self-running power generated by said drive motor up to a value corresponding to the amount of the self-running operation.

FIG. 1






FIG. 2

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10







FIG. 11






FIG. 12

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 129 932 A3

(12)

## EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
19.05.2004 Bulletin 2004/21

(51) Int Cl.7: B62M 23/02

(43) Date of publication A2:  
05.09.2001 Bulletin 2001/36

(21) Application number: 01103471.7

(22) Date of filing: 14.02.2001

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventor: Sakagami, Koji, c/o K.K. Honda Gijutsu  
Kenkyusho  
Wako-shi, Saitama (JP)

(74) Representative: Liska, Horst, Dr.-Ing. et al  
Weickmann & Weickmann  
Patentanwälte  
Postfach 86 08 20  
81635 München (DE)


(30) Priority: 01.03.2000 JP 2000055085

(71) Applicant: Honda Giken Kogyo Kabushiki Kaisha  
Minato-ku, Tokyo (JP)

## (54) Motor-driven bicycle

(57) The invention provides a motor-driven bicycle including an automatic gear shifter, which is capable of improving a shift feeling upon gear-shift and controlling a self-running power of a drive motor determined on the basis of an amount of a self-running operation by a driver as a function of a braking state and a vehicle speed. To achieve this, a motor-driven bicycle includes a drive motor M for generating a self-running power in response to a self-running operation by a driver, a gear shifter connected between the drive motor M and a drive wheel, and means for detecting a vehicle speed. This motor-

driven bicycle further includes a self-running reference duty ratio map 201 for determining a self-running power to be generated by the drive motor M, that is, a duty ratio of an AC exciting current to be supplied to the drive motor M on the basis of an operated amount of a self-running operation by a driver, a gear step of the gear shifter, and a vehicle speed. In the self-running reference duty ratio map 201, a reference duty ratio Dref1 of a drive current to be supplied to the drive motor M at the time of self-running is previously registered as a function of a throttle angle  $\theta_{th}$  detected by a throttle opening sensor 15.





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 01 10 3471

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 222 179 A (BINDER AVIAT GMBH) 20 May 1987 (1987-05-20)	8-12	B62M23/02
A	* the whole document *	1	
X	EP 0 976 649 A (SONY CORP) 2 February 2000 (2000-02-02)	8	
A	* figures 1,3 *	1	
A	PATENT ABSTRACTS OF JAPAN vol. 1998, no. 01, 30 January 1998 (1998-01-30) & JP 09 240564 A (YAMAHA MOTOR CO LTD), 16 September 1997 (1997-09-16) * abstract; figures *	1,8	
D,A	PATENT ABSTRACTS OF JAPAN vol. 1998, no. 02, 30 January 1998 (1998-01-30) & JP 09 263289 A (YAMAHA MOTOR CO LTD), 7 October 1997 (1997-10-07) * abstract; figures *	1,8	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	EP 0 937 638 A (YAMAHA MOTOR CO LTD) 25 August 1999 (1999-08-25) * paragraph [0063] - paragraph [0085]; figures *	1,8	B62M
A	US 5 937 964 A (TERR SETH A ET AL) 17 August 1999 (1999-08-17) * column 3 - column 17; figures *	1,8	
The present search report has been drawn up for all claims			
Place of search <b>MUNICH</b>		Date of completion of the search <b>18 March 2004</b>	Examiner <b>Jung. W</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P04C01)



European Patent  
Office

Application Number

EP 01 10 3471

### CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

### LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☐ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☒ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent  
Office

LACK OF UNITY OF INVENTION  
SHEET B

Application Number  
EP 01 10 3471

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. Claims: 1-7

A motor-driven bicycle including a drive motor (M), a gear shifter (19) connected between said drive motor (M) and a drive wheel (31), and means for detecting a vehicle speed, whereby said motor-driven bicycle further includes self-running power determining means (20) for determining a self-running power of said drive motor on the basis of

an operated amount of the self-running operation,  
a gear step of said gear-shifter,  
and a vehicle speed (V).

2. Claims: 8-12

A motor-driven bicycle including a drive motor (M) whereby said bicycle includes during-braking control means (210) for controlling the self-running power of the drive motor (M) on the basis of

a braking operation and  
a vehicle speed (V).

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 10 3471

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-03-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0222179	A	20-05-1987	AT 51826 T	15-04-1990
			DE 3623800 A1	30-04-1987
			DE 3670258 D1	17-05-1990
			EP 0222179 A1	20-05-1987
			GR 3000456 T3	28-06-1991
EP 0976649	A	02-02-2000	JP 10035576 A	10-02-1998
			EP 0976649 A2	02-02-2000
			DE 69711342 D1	02-05-2002
			DE 69711342 T2	21-11-2002
			EP 0846614 A1	10-06-1998
			WO 9745316 A1	04-12-1997
			TW 470037 Y	21-12-2001
			US 6247548 B1	19-06-2001
			US 2003047369 A1	13-03-2003
JP 09240564	A	16-09-1997	NONE	
JP 09263289	A	07-10-1997	NONE	
EP 0937638	A	25-08-1999	JP 11227663 A	24-08-1999
			EP 0937638 A2	25-08-1999
US 5937964	A	17-08-1999	AU 6757398 A	12-10-1998
			BR 9808403 A	16-05-2000
			EP 0968113 A1	05-01-2000
			TW 402570 B	21-08-2000
			WO 9841438 A1	24-09-1998
			US 6269898 B1	07-08-2001
			US 6516911 B1	11-02-2003

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**THIS PAGE BLANK (USPTO)**